

ASC1204C-S

Four Door Access Controller





Features

- Support 100,000 valid cards & 150,000 records
- · Support multiple cards
- Support card, password, fingerprint and combination
- TCP/IP interface to PC
- Wiegand or RS-485 interface to readers(4 door)
- Door time out alarm, intrusion alarm, duress alarm and tamper alarm
- · Anti-passback, multi-door interlock, multi-card open
- Support 128 efficient time and holiday schedules
- · Watch dog function ensure device free from halting
- Surface mounted installation
- Accumulator battery extension









Technical Specification

System

Main Processor	32 Bit
Memory	16M

Input/Output Ports

Input	Inputs x 9 (door sensor x 4, exit button x 4, alarm x 1)
Output	Relay x 5(door lock x 4, alarm x 1)
Reader	Reader x 4

Capacity

Period

Card holders/Events

Function	
Access control	Anti-passback, Multi-interlock, Multi-card unlock
User Management	General, VIP, Guest, Patrol, Black list, Duress
Alarm Function	Door time out alarm, Intrusion alarm, Duress alarm, Tamper alarm

Support 128 groups of schedule, 128 groups of

period and 128 groups of holiday period

100,000/150,000


Interface

To PC	RJ45(10/100M)
To Reader	Wiegand/ RS485

Genreal

Gerriear	
RTC	Yes
Power Supply	9-15DC/500mA
Working Environment	-30°C~+60°C
Working Humidity	≤95%
Dimension(W×D×H)	280*114*320mm
Weight	2Kg

Dimensions





Application

Multi-door Management Four door controller

