

# N6078 Bullet Network Camera



## 2 Megapixel / H.264 / 720P Real-Time / IR / Vari-Focal


- 2 Megapixel 1/3" CMOS Sensor in High Resolution
- H.264/MJPEG Dual Codec & Streaming simultaneously
- Vari-Focal Lens 3mm-10mm F1.6
- UXGA (1600x1200@15fps) / WXGA (1280x720@30fps)
- Digital I/O for External Sensor and Alarm
- Mechanical ICR
- Built-in IR Illuminator
- 3D Noise Reduction
- 2 Way Audio Supported
- Intelligent Video Analytics
- Micro SD Card Supported (SDHC up to 32GB)
- IP 66 Water Proof
- PoE Power Over Ethernet IEEE802.3af (Option)



### Specifications

<b>Camera</b>		<b>Network</b>	
Sensor	2 Mega Pixel 1/3" CMOS sensor	Streaming Protocols	RTSP/RTP/UDP, RTSP/RTP/TCP, RTSP/RTP/HTTP tunneling, LAN Multicast, Multipart-JPEG
Scan Method	Progressive	Supported Protocols	IPv4, HTTP, UDP, TCP, ICMP, IGMP, ARP, DHCP, NTP, SMTP, FTP, SAMBA, UPnP, PPPoE, DNS, DDNS, RTSP, RTP, RTCP, ONVIF
Lens	Vari-Focal Lens 3-10mm F1.6	Mobile Surveillance	Yes
Number of Effective Pixel (H*V)	1600x1200	Storage	
Minimum Illumination	0.1Lux (F1.6, AGC max.) 0Lux (IR On)	External	1x Micro SD Card (SDHC up to 32GB)
Horizontal Resolution	950TVL	Processors and Memory	
Dynamic Range	71db	CPU	ARM9 SOC
SNR (max.)	42.3db	Flash and Memory	16MB NOR flash, 256MB DDRII
DNR	Auto	I/O and Connectors	
White Balance	Auto	LAN	1x RJ-45 Ethernet connector
Gain Control	High/Middle/Low, 3 steps selection	Audio	1x Audio Line-in, 1x Audio Line-out
Flicker Control	Off/50Hz/60Hz, 3 steps selection	Alarm I/O	1x Alarm-in, 1x Alarm-out
Backlight Compensation	On/Off	Software Compatibility	
Electronic Shutter	Auto/Slow shutter (2X~16X / 5 steps selection)	Browser	Internet Explorer 6.0 or above
Number of the Preset Positions	16	Application Software	VMS Application Software
		OS supported	Microsoft Windows 2000, XP, Vista, Windows 7
		Open API	CGI commands to control camera Media SDK to handle streaming
		Factory Default	Button
		Power	DC 12V DC12V/ POE
		Power Consumption	6W (IR On) / 4W (IR Off)
		Dimension	180mm(L) x 65mm(Ø)
		Weight	DC12V : 607g / PoE : 627g
		Operating Environment	Operating temperature -20°C~ +50°C Storage temperature -30°C~ +60°C
		Certification	Operation humidity 0%~95% Non-condensing
		Warranty	CE, FCC Class A, RoHS, IP66
			24 months

### Dimension Diagram



### Distributed by:

### 3PocketNet Technology Inc.

7F., No.5, Lane 16, Sec. 2, Sichuan Rd. Banqiao Dist.,  
New Taipei City 22061, Taiwan (R.O.C.)  
Tel: +886.2.8967.2909  
Fax: +886.2.8967.2779